## HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

## TECHNICAL DATA SHEET

TECHNICAL DATA SHEET	
PRODUCT NAME	FAST SCARLET 2BSP
CHEMICAL NATURE	MONOAZO
CHEMICAL FORMULAR	$C_{18}H_{11}CIN_2O_6SSr$
COLOR INDEX NAME	PIGMENT RED 48:3 (15865:3)
CAS NO.	15782-05-5
STRENGTH	100±2%
PHYSICAL PROPERTIES	
PH AQUEOUS EXTRACT	7.0-8.5
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	≤2.0%
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY RED POWDER
SPECIFIC GRAVITY	1.80g/cm <sup>3</sup>
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105℃	<3.0%
FASTNESS PROPERTIES	
LIGHT FASTNESS	8
HEAT FASTNESS	200℃
WATER RESISTANCE	5
OIL RESISTANCE	5
ACID RESISTANCE	5
ALKALI RESISTANCE	4
TECHNICAL PROPERTIES	
Easing dispersing, good migration resistance.	
<u>APPLICATION</u>	
It's mainly used for PVC, Fiber, EVA, PE and powder coating.	
Suggested for RUB.	
NOTE	

The above information is provided as guidelines for your reference only. The accurate effects should be based on the test results in laboratory.