

the test results in laboratory.

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET

TECHNICIE DITTIONEE	
PRODUCT NAME	LAKE RED C
CHEMICAL NATURE	MONOAZO
CHEMICAL FORMULAR	$C_{20}H_{13}N_{20}O_4S1/2Ba$
COLOR INDEX NAME	PIGMENT RED 53:1(15585:1)
CAS NO.	5160-02-1
STRENGTH	100 <u>+</u> 2%
PHYSICAL PROPERTIES	
PH AQUEOUS EXTRACT	7.0-8.0
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	≤2.0%
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY RED POWDER
SPECIFIC GRAVITY	1.80g/cm ³
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105℃	<3.0%
FASTNESS PROPERTIES	
LIGHT FASTNESS	6
HEAT FASTNESS	160℃
WATER RESISTANCE	4
OIL RESISTANCE	4
ACID RESISTANCE	4
ALKALI RESI <mark>STANC</mark> E	4
TECHNICAL PROPERTIES	
Yellowish shade, high glossy, high tinting strength.	
<u>APPLICATION</u>	
It's mainly used for offset ink and water based ink, PE, PVC.	
<u>NOTE</u>	

The above information is provided as guidelines for your reference only. The accurate effects should be based on