

## HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET	
PRODUCT NAME	LITHOL RUBINE BK
CHEMICAL NATURE	MONOAZO
CHEMICAL FORMULAR	$C_{18}H_{12}N_2O_6SCa$
COLOR INDEX NAME	PIGMENT RED 57:1 (15850:1)
CAS NO.	5281-04-9
STRENGTH	100±2%
PI	HYSICAL PROPERTIES
PH AQUEOUS EXTRACT	7.0-8.0
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	<u>≤2.0%</u>
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY RED POWDER
SPECIFIC GRAVITY	1.70g/cm <sup>3</sup>
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105℃	<3.0%
<u>FA</u>	ASTNESS PROPERTIES
LIGHT FASTNESS	5
HEAT FASTNESS	180°C
WATER RESISTANCE	5
OIL RESISTANCE	3
ACID RESISTANCE	4
ALKALI RESISTANCE	4
TE	CHNICAL PROPERTIES
Bluish shade, high glossy, high tinting strength.	
	APPLICATION
It's mainly used for offset ink and wa	iter based ink, PE, PVC.
Suggested for industrial paint, solvent based ink.	
	<u>NOTE</u>
The above information is provided as guideli	ines for your reference only. The accurate effects should be based on
the test results in laboratory.	