

## HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECH	INICAL DATA SHEET
PRODUCT NAME	LITHOL RUBINE 4BP
CHEMICAL NATURE	MONOAZO
CHEMICAL FORMULAR	C <sub>18</sub> H <sub>12</sub> N <sub>2</sub> O <sub>6</sub> SCa
COLOR INDEX NAME	PIGMENT RED 57:1 (15850:1)
CAS NO.	5281-04-9
STRENGTH	100±2%
<u>PH</u>	<u>YSICAL PROPERTIES</u>
PH AQUEOUS EXTRACT	7.0-8.0
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	<u>&lt;2.0%</u>
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY RED POWDER
SPECIFIC GRAVITY	1.70g/cm <sup>3</sup>
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105°C	<3.0%
<u>FA</u>	STNESS PROPERTIES
LIGHT FASTNESS	6
HEAT FASTNESS	220°C
WATER RESISTANCE	4
OIL RESISTANCE	4
ACID RESISTANCE	4
ALKALI RESISTANCE	4
TEC	CHNICAL PROPERTIES
Bluish shade, easing dispersing, good	migration resistance.
	APPLICATION
It's mainly used for PVC , Fiber, EVA	, PE and powder coating.
Suggested for RUB.	
	NOTE
The above information is provided as guidelin	nes for your reference only. The accurate effects should be based on
the test results in laboratory.	