## HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

## TECHNICAL DATA SHEET

TECHN	ICAL DATA SHEET		
PRODUCT NAME	PERMANENT RED F5RK		
CHEMICAL NATURE	MONOAZO		
CHEMICAL FORMULAR	C <sub>26</sub> H <sub>22</sub> N <sub>4</sub> O <sub>4</sub>		
COLOR INDEX NAME	PIGMENT RED 170 (12475)		
CAS NO.	2786-76-7		
STRENGTH	100±2%		
PHYS	ICAL PROPERTIES		
PH AQUEOUS EXTRACT	6.0		
RESIDUE ON SIEVE (100 um)	≤3.0%		
WATER SOLUBLE MATTER	≤2.0%		
SOLUBLE IN WATER	INSOLUBLE		
ODOUR	NONE		
PHYSICAL FORM	DRY RED POWDER		
SPECIFIC GRAVITY	1.36g/cm <sup>3</sup>		
OIL ABSORPTION	≤45g/100g		
VOLATILE AT 105°C	<3.0%		
FAST	NESS PROPERTIES		
LIGHT FASTNESS	8		
HEAT FASTNESS	180℃		
WATER RESISTANCE	5		
OIL RESISTANCE	5		
ACID RESISTANCE	5		
ALKALI RESISTANCE	5		
TECHN	NICAL PROPERTIES		
Bluish shade, excellent light fastness, high covering power, good solvent resistance.  APPLICATION  It's mainly used for inks, PVC, Fiber, PP, PE, industrial paint, coil coating and OEM paint.			
		Suggested for DII DIID DC DC DA doe	anative naint neved as acting

Suggested for PU, RUB, PS, PC, PA, decorative paint, powder coating.

## **NOTE**

The above information is provided as guidelines for your reference only. The accurate effects should be based on the test results in laboratory.