

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET

TECHNICAL DATA SHEET	
PRODUCT NAME	PERMANENT ORANGE 2G
CHEMICAL NATURE	MONOAZO
CHEMICAL FORMULAR	$C_{16}H_{10}N_4O_5$
COLOR INDEX NAME	PIGMENT ORANGE 5 (12075)
CAS NO.	3468-63-1
STRENGTH	100±2%
PHYSICAL PROPERTIES	
PH AQUEOUS EXTRACT	5.0-6.0
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	≤2.5%
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY ORANGE POWDER
SPECIFIC GRAVITY	1.55g/cm ³
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105℃	<3.0%
<u>FASTNESS PROPERTIES</u>	
LIGHT FASTNESS	7
HEAT FASTNESS	150℃
WATER RESISTANCE	4
OIL RESISTANCE	4
ACID RESISTANCE	4
ALKALI RESISTANCE	4
TECHNICAL PROPERTIES	
Reddish shade, semi-transparent, high tinting strength.	
A DRIVING ATTION	

APPLICATION

It's mainly used for industrial paint, decorative paint, coil coating, textile printing and water-based inks.

Suggested for offset ink, PA ink, NC ink, PP ink.

NOTE

The above information is provided as guidelines for your reference only. The accurate effects should be based on the test results in laboratory.