

## HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET			
PRODUCT NAME	PERMANENT ORANGE G		
CHEMICAL NATURE	DISAZO		
CHEMICAL FORMULAR	C <sub>32</sub> H <sub>24</sub> Cl <sub>2</sub> N <sub>8</sub> O <sub>2</sub>		
COLOR INDEX NAME	PIGMENT ORANGE 13 (21110)		
CAS NO.	3520-72-7		
STRENGTH	100±2%		
<u>P1</u>	HYSICAL PROPERTIES		
PH AQUEOUS EXTRACT	6.0-7.0		
RESIDUE ON SIEVE (100 um)	≤3.0%		
WATER SOLUBLE MATTER	<u>≤2.5%</u>		
SOLUBLE IN WATER	INSOLUBLE		
ODOUR	NONE		
PHYSICAL FORM	DRY ORANGE POWDER		
SPECIFIC GRAVITY	1.50g/cm <sup>3</sup>		
OIL ABSORPTION	≤45g/100g		
VOLATILE AT 105℃	<3.0%		
<u> </u>	ASTNESS PROPERTIES		
LIGHT FASTNESS	4		
HEAT FASTNESS	180°C		
WATER RESISTANCE	4		
OIL RESISTANCE	4		
ACID RESISTANCE	4		
ALKALI RESISTANCE	4		
TECHNICAL PROPERTIES			
Reddish shade, semi-transparent, high glossy, low viscosity. <u>APPLICATION</u> It's mainly used for offset inks, textile printing and PE.   Suggested for PA inks, NC inks, PP inks, water based inks, Industrial paint and water based			
		decorative paint.	
		NOTE	
		The above information is provided as guidel	ines for your reference only. The accurate effects should be based on
the test results in laboratory.			