

# HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

## TECHNICAL DATA SHEET

PRODUCT NAME	PERMANENT ORANGE GRN
CHEMICAL NATURE	DISAZO
CHEMICAL FORMULAR	C <sub>34</sub> H <sub>32</sub> N <sub>6</sub> O <sub>6</sub>
COLOR INDEX NAME	PIGMENT ORANGE 34 ( 21160)
CAS NO.	6505-28-8
STRENGTH	100 <u>+</u> 2%
PHYSI	CAL PROPERTIES
PH AQUEOUS EXTRACT	5.0-7.5
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	≤2.5%
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY ORANGE POWDER
SPECIFIC GRAVITY	1.45g/cm <sup>3</sup>
OIL ABSORPTION	≤54g/100g
VOLATILE AT 105℃	<3.0%
FASTNESS PROPERTIES	
LIGHT FASTNESS	6
HEAT FASTNESS	160°C
WATER RESISTANCE	4
OIL RESISTANCE	4
ACID RESISTANCE	4
ALKALI RESISTANCE	4
TECHNICAL PROPERTIES	
Reddish shade, high transparent.	

## **APPLICATION**

It's mainly used for offset ink, water based ink and EVA, PE, Industrial paint, water decorative paint, textile printing.

Suggested for PA ink, NC ink, PP ink, PVC plastic.

## **NOTE**

The above information is provided as guidelines for your reference only. The accurate effects should be based on the test results in laboratory.