

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET

PRODUCT NAME	PERMANENT ORANGE F2L
CHEMICAL NATURE	DISAZO
CHEMICAL FORMULAR	C ₃₄ H ₂₈ Cl ₂ N ₈ O ₂
COLOR INDEX NAME	PIGMENT ORANGE 34 (21115)
CAS NO.	15793-73-4
STRENGTH	100 <u>+</u> 2%
PHYSICAL PROPERTIES	
PH AQUEOUS EXTRACT	4.5-6.5
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	≤2.5%
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY ORANGE POWDER
SPECIFIC GRAVITY	1.40g/cm ³
OIL ABSORPTION	≤79g/100g
VOLATILE AT 105°C	<3.0%
FASTNESS PROPERTIES	
LIGHT FASTNESS	6
HEAT FASTNESS	180°C
WATER RESISTANCE	4
OIL RESISTANCE	4
ACID RESISTANCE	4
ALKALI RESI <mark>STANC</mark> E	4
TECHNICAL PROPERTIES	
Reddish shade, high transparent, high glossy, low viscosity	
<u>APPLICATION</u>	
It's mainly used for NC ink, PA ink, PP ink.	
Suggested for solvent-based paint, coating.	
<u>NOTE</u>	
The above information is provided as guidelines for your reference only. The accurate effects should be based on	

The above information is provided as guidelines for your reference only. The accurate effects should be based on the test results in laboratory.